

# Photocopy This Form Use one form for each product

type you are selecting.

This form may also be completed online at gemssensors.com for RFQ.

This is a ☐ Request for a Quote ☐ Order P.O.#	Name		
	Company		
Quantity Needed	Street		
Date Required/	City	State	_ Zip
Shipping Method: Partials Accepted: ☐ Yes	Phone ( )		
□ No	Fax ( )		

## **DIPTAPE Level Indicators**

**Application Environment Conditions** This information is essential to the accurate and proper operation of your DipTape Level Indicators. Please complete fully and accurately.

1. Liquid Media:		
2. Pressure: Minimumpsig	Maximum	psig
3. Temperature: Minimum °F	Maximum	°F
4. Specific Gravity: Minimum	Maximum	

5. Viscosity:	SSU
6. Tank Material:	
7. Tank Denth:	

1. Mounting Type	1.	M	loun	iting	Ty	pe:
------------------	----	---	------	-------	----	-----

⊔ Type B	□ Type C
□ Type 3	☐ Type 4

#### 2. Material:

□ PVC	$\square$ PVDF		□ Polypropylene
□ Brass	□ 316 S	tainless	Steel
Flange – Alloy Version:			
☐ 316 Stainless	Steel	□ Carb	on Steel

### 3. Float Types:

Quote: \$ \_\_

□ PVC	□ PVDF	□ Polypropylene
□ Buna N	$\hfill\Box$ 316 Stainless Steel	

#### 4. Stem Length (Length Overall) "B"

Dimension B =	□ centimeters
Max. indicating length 72".	
Other lengths, consult factory	

Please contact Gems for any configuration or special requirements not covered on this form. 800-378-1600

Date Quoted:\_\_\_/\_



**Gems Sensors & Controls** One Cowles Road Plainville, CT 06062-1198

860.747.3000 860.747.4244 fax www.gemssensors.com