

Large Size – Alloys

LS-800 Series

The General Purpose Workhorse for Water and Oils

- ▶ Stainless Steel or Brass Mountings
- ▶ 1 to 6 Actuation Levels
- ▶ Lengths to over 11 feet (3.4 m)
- ▶ CSA Listed

Rugged construction and multiple options provide the LS-800 Series with exceptional versatility. Longer and more substantial than other metallic models, the LS-800 is capable of supporting larger, more buoyant floats, and is physically stronger for better reliability in contaminated or turbulent media. This series offers SPST or SPDT switches, and a choice of mountings, floats and materials that can be configured for a wide range of applications in water, oils, chemicals and corrosive liquids.

Temperature Sensing

To save space and simplify wiring, GEMS can incorporate a temperature sensor in the end of the float stem on any model type LS-800. Two sensor types are available: Transducers for continuous output, and Thermostats for switch actuation. See Page B-23 for details.



Adjustable Mounting

Allows stem to travel up and down for fine tuning your actuation points. See next page.



LS-800 switches are U.L. Approved for Class I, Division 2, Groups B, C, D hazardous locations

1. Mounting Types


Each mounting type can be configured with stem lengths (L_f) and float material indicated in the table below. Mountings are also continued on following page.

Note: Sanitary flange mountings are also available, but not shown. Please contact factory.

| | Type 1 1/2" NPT | Type 8 1" NPT | Type 2 1-1/4" NPT | Type 3 2" NPT | Type 4 3", 150# Dia. Flange |
|---------------------------------------|--|----------------------|----------------------|-----------------------|--|
| in (mm) | | | | | |
| Stem & Mounting Material | Brass or 316 Stainless Steel | | | | Flange: Carbon Steel or 316 S.S. Stem: 316 S.S. |
| Max. Length (L_f) | 36 inches (91.4 cm) | 60 inches (152.4 cm) | | 140 inches (355.6 cm) | |
| Mounting Position | Vertical ±30° Inclination | | | | |
| Float Stops* | Brass Units: Beryllium Copper Grip Rings; Stainless Steel Units: S.S. ARMC0 PH-15-7MO Grip Rings | | | | |

* Units greater than 72" overall length are supplied with collars with setscrews (made of same material as stem and mounting) in place of float-stop rings. Collars are optional on units less than 72" overall length. Units requiring 316 SS float stops must be special ordered with 316 SS collars instead of grip rings. In some instances, concentration of chlorine and other corrosive compounds in the media require the use of collar type float stops. Consult factory for details.


ORDER IT!
Ordering is Easy! See Page B-24.
Easy online ordering too!



LS-800 Series – Continued

1. Mounting Types – continued

Type 5 External Mounting units are ideal for tanks with limited access to tops or bottoms.



| | | |
|---------------------------------------|---------------------|----------------------|
| Housing Material | Brass | 316 Stainless Steel |
| Stem & Mounting Material | Brass | 316 Stainless Steel |
| Port Sizes | 3/4" NPT | |
| Maximum Length (L₀) | 120 inches (305 cm) | |
| Float Stops* | Beryllium Copper | S.S. ARMCO PH-15-7MO |

* Units greater than 72" overall length are supplied with collars with setscrews (made of same material as stem and mounting) in place of float-stop rings. Collars are optional on units less than 72" overall length. Units requiring 316 SS float stops must be special ordered with 316 SS collars instead of grip rings. In some instances, concentration of chlorine and other corrosive compounds in the media require the use of collar type float stops. Consult factory for details.

2. Float Types

A single float type is selected for use at all actuation points. Be sure, by reviewing the table below, that the desired float is compatible with the Mounting Type selected in Step 1.

| Float Material | Buna-N | | | | 316 Stainless Steel | | |
|------------------------------------|--|--------------|--------------|----------------------|-----------------------------------|----------------------|---------------|
| Compatible Mounting Types | 1, 2, 3, 4, 8 | 2 | 1, 3, 4, 5 | 3, 4, 5 (Units >72") | 1, 3, 4, 5 (Units ≤72") | 3, 4, 5 (Units >72") | 1, 3, 4 |
| Float Dimensions (in (mm)) | | | | | | | |
| Part Number | 253644 | 26032 | 10558 | 24864 | 14569 | 15666 | 138935 |
| Operating Temperature | Water: to 180°F (82°C) Oil: -40°F to +230°F (-40°C to +110°C) | | | | -40°F to +300°F (-40°C to +149°C) | | |
| Min. Media Specific Gravity | 0.55 | 0.75 | 0.55 | 0.55 | 0.75 | 0.75 | 0.80 |

Maximum Pressure Ratings Chart


| Mounting Type | | Float Part Number | | | | | | |
|---------------|----------|---------------------------------|--------------------|-------|-------|--------------------|--------------------|--------------------|
| | | 253644 | 26032 | 10558 | 24864 | 14569 | 15666 | 138935 |
| | | 1, 2, 3 | 150 psi (10.3 bar) | | | | 750 psi (51.7 bar) | 300 psi (20.7 bar) |
| 5 | 4 | 150 psi (10.3 bar) | | | | | | 180 psi (12.4 bar) |
| | Brass | 100 psi (6.9 bar) @ 70°F (21°C) | | | | | | |
| | 316 S.S. | 150 psi (10.3 bar) | | | | 750 psi (51.7 bar) | 300 psi (20.7 bar) | 120 psi (8.3 bar) |

Review the Compatible Mounting Type row in the "Float Types" table above this matrix for produceable mounting/float combinations. Not all combinations implied by this Pressure Rating Chart are possible or recommended.

LS-800-A Series Adjustable Mounting Available for LS-800 Series Mounting Types 2, 3 and 4.

Special cinch-nut on mounting allows stem to travel up or down for fine tuning the actuation points. The extent of adjustment depends on unit length and distance from mounting to highest float stop. When ordering, specify "LS-800-A" as Series Type.

Note: Maximum overall length is limited to 72" with this option.



Intrinsically-Safe Relays

Using Gems SAFE-PAK® relays and barriers, these switches provide automatic refills/pumpdown and are intrinsically-safe without explosion-proof housing and piping.



See Section L

LEVEL SWITCHES – MULTI POINT

3. Electrical Specifications

Switch (N.O. or N.C.):

SPST: 20 VA or 100 VA


SPDT: 20 VA

Lead Wires: 18 AWG, 24" L., Polymeric (except as noted in Wiring Color Code chart at right).

Approvals: LS-800 Series switches are U.L. Recognized – File No. E45168; CSA Listed – File No. 30200

Typical Wiring Diagrams

For clarity, only two actuation levels are shown in each group diagram.



Wiring Color Code


Tinted area designates U.L. Recognized wiring configurations.

| Wiring | SPST Switches | | | SPDT Switches 20 VA | | | | |
|----------------------|---------------|----------|--------|---------------------|---------|----------|---------|------------|
| | Group I | Group II | | Group III | | Group IV | | |
| Com. Wire | Black | None | | Black | | None | | |
| | NO/NC | SW. Com. | NO/NC | NO | NC | SW. Com. | NO | NC |
| L₁ | Red | Red | Red | Red | Wh/Red | Red | Wh/Red | Wh/Blk/Red |
| L₂ | Yellow | Yellow | Yellow | Yellow | Wh/Yel | Yellow | Wh/Yel | Wh/Blk/Yel |
| L₃ | Blue | Blue | Blue | Blue | Wh/Blue | Blue | Wh/Blue | Wh/Blk/Blu |
| L₄ | Brown | Brown | Brown | Brown | Wh/Brn | Brown | Wh/Brn | Wh/Blk/Brn |
| L₅ | Orange | Orange | Orange | Orange | Wh/Orn | Orange | Wh/Orn | Wh/Blk/Orn |
| L₆ | Gray | Gray | Gray | Gray | Wh/Gra | Gray | Wh/Gra | Wh/Blk/Gra |

Notes:

1. Non-U.L. Recognized units (white areas) use 22 AWG, 24" L., PTFE Lead wires.
2. Units with 100 VA switches are not U.L. Recognized or CSA Listed.
3. See "Electrical Data" on Page X-5 for more information.

4. Actuation Level Dimensions



* Actuation level distances and L₀ (overall unit length) are measured from inner surfaces of mounting plug or flange.
 ** Length Overall L₀ = L₁ + Dimension B.
 See Mounting Types for Maximum Length values.

Switch actuation levels are determined following the guidelines below.

All units 72" or less L₀ with Stainless Steel or Buna-N floats. Also any unit over 72" L₀ with Buna-N floats:

A = 1-1/2" (38.1 mm) minimum distance to highest level (2", Type 5 only).

B = 2" (50.8 mm) minimum distance from end of unit to lowest level.

C = 3" (76.2 mm) minimum distance between levels.

D = 1/4" (6.3 mm) minimum distance between actuation levels (Note: One float for two levels can be used only when low level is N.C. dry and high level is N.O. dry).

Types 1, 3, 4, and 5 units with stainless steel float, Part Number 15666:

A = 1-5/8" (41.3 mm) minimum distance to highest level (2", Type 5 only).

B = 2-1/2" (63.5 mm) minimum distance from end of unit to lowest level.

C = 4" (101.6 mm) minimum distance between level.

D = 1/4" (6.3 mm) minimum distance between actuation levels (Note: One float for two levels can be used only when low level is N.C. dry and high level is N.O. dry).

Notes:


1. A, B and C dimensions based on a liquid specific gravity of 1.0.
2. One float for two levels can be used only when 20 VA switch is used.
3. Actuation levels are calibrated on descending fluid level, with water as the calibrating fluid, unless otherwise specified.
4. Tolerance on actuation levels is ±1/8" (3.2 mm).
5. TH (Temperature option) makes "B" dimension a minimum of 2.75" (69.8 mm).

Optional Integrated Temperature Sensors

- ▶ Compatible with LS-700 and LS-800 Series Units
- ▶ Thermostat Switches or Thermistor Versions

Advantages of integrated temperature sensors:

- Space Saving.
- Fewer intrusions into the tank.
- Electrical wiring emanates from a single source – eliminate multiple conduits.
- Economical – typically less expensive than separate sensors.



Thermistor for Continuous Indication – TM-800 and TM-700

- ▶ Excellent repeatability

Value: 10,000 ohms @ 77°F (25°C)

Tolerance: ±0.2°C from 32°F to 158°F (0°C to 70°C)

Operating Temperature: 302°F (150°C), Max.


Alpha @ 25°C: -4.39%/°C

Dissipation Constant: 1mW/°C in Still Air;
8mW/°C in Oil Bath.


How to Order

Temperature thermistors are available on LS-700 Series units with up to three actuation levels, and on LS-800 Series units with up to five actuation levels. To have thermistor added, order model TM-800 or TM-700.

Note: This option is not CE Approved.



GROUP I



GROUP II

Thermostat for Switch Actuation

- Standard Settings from 100°F to 200°F.
- Open or close switch on increasing temperature.

Use these switches to set off High/Low temperature alarms. Or, combine with GEMS relays to control tank heating and cooling, motor-operated valves, etc.


To designate the thermostat switch option, order model TH-700 or TH-800.

Also specify the choice from selections A, B and C below.

- Switch Rating:**
For LS-800 Series: 6A/120V, 4A/240V, 100VA (non-inductive).
For LS-700 Series: 2.6A/120V (inductive).
- Contact Operation on Increasing Temperature:**
“Opens” when Set Point reached or “Closes” when Set Point reached.
- Standard Temperature Set Point (±7.2°F; ±4°C):**
100°F (37.7°C), 125°F (51.6°C), 150°F (65.6°C), 175°F (79.4°C), 200°F (93.3°C)


Notes:

1. Other temperature settings and tolerances available; 25 piece minimum order quantity applies. Please call GEMS Sensors Inc. for more information.
2. This option is not CE Approved.




Note: End of unit stem must be submerged a minimum of 2-3/4" for level switch actuation.

Typical Wiring Diagram



GROUP I



GROUP II